

## Oil heating for lubricant circuit

**Publication number:** EP0899501

**Publication date:** 1999-03-03

**Inventor:** EKMAN HANS (DE)

**Applicant:** SAFEMATIC SCHMIERTECHNIK GMBH (DE)

**Classification:**


- international: **F16N39/04; F28F13/12; F16N39/00; F28F13/00;** (IPC1-7): F16N39/04; F28F13/12

- European: F16N39/04; F28F13/12

**Application number:** EP19970114726 19970826

**Priority number(s):** DE19961034454 19960826

**Also published as:**

 DE19634454 (A1)

**Cited documents:**


 US4793407  
 EP0781623  
 US5072784  
 US1511250

[Report a data error here](#)

Abstract not available for EP0899501

Abstract of corresponding document: **DE19634454**

The oil heating arrangement is for a circulation system and comprises a container (1) which is arranged between the return and output of the oil. The oil is heated by a heater (19) which uses hot water or low pressure steam as its heat carrier. There is a heat exchanger in the bottom of the container, arranged on the heat carrier side so that a turbulent flow of the heat carrier takes place in the heat exchanger. The heat exchanger may be of the plate type, with narrow passages on the heat-carrier side.



Data supplied from the **esp@cenet** database - Worldwide